



Cable glands from metal

Cable gland: Ex e or Ex d off brass type PNE, PNA are used for unarmoured cable with outer sealing ring. Also available for armoured cable.

Technical specifications

Explosion protection

Ex II 2 GD Ex d IIC

Norm

EN 60079 - 1, 60079 - 7

Protection

IP66

Material

Brass (brass nickel plated, alloy or stainless steel on request)

Certificate

INERIS 03ATEX0140X



Cable [mm]	Thread size UNI 6125 NPT	Thread size metric
5.5 - 8	1/2"	M20 x 1.5
8 - 10.5	1/2"	M20 x 1.5
10.5 - 13	1/2"	M20 x 1.5
10.5 - 13	3/4"	M25 x 1.5
13 - 15.5	3/4"	M25 x 1.5
15.5 - 18	3/4"	M25 x 1.5
15 - 18	1"	M32 x 1.5
18 - 21	1"	M32 x 1.5
21 - 24	1"	M32 x 1.5
21 - 24	1 1/4"	M40 x 1.5
24 - 27	1 1/4"	M40 x 1.5
27 - 30	1 1/4"	M40 x 1.5
24 - 27	1 1/2"	M50 x 1.5
27 - 30	1 1/2"	M50 x 1.5
30 - 33	1 1/2"	M50 x 1.5
33 - 36	1 1/2"	M50 x 1.5