



LED signal lamp bundle

Bright inexpensive installation signal lamp with a lifespan of more than 10 years. Intrinsically Safe certified according to ATEX and FM or in industrial design in red, yellow, green, blue and white.

BA 390 has 20mA constant current.

BA 390S has full brightness even at 4mA. Connection at the terminals at the back of the cabinet doors.

For applications with high degree of protection of the connection points of view, there is an option a screw-on accessory kit BA 599, which guarantees the protection IP65.

Technical specifications

BA 390 / BA 390S

Explosion protection

Ex [ia] II C T4 (Zone 0, 1 and 2)

Certification

BAS 01 ATEX 1062X

Voltage

14V / 8V

Current

20mA / 4 mA

Technical specifications

BA 590 / BA 591 / BA 592

Voltage

24V DC / 115 V AC / 230V AC

Current

20mA

Protection

Front IP66



Ex i area		Secure area			Colour	Lux	S - type lux
20 mA	4 mA	24 V DC	115 V AC	230 V AC			
BA 390R	BA 390RS	BA 590R	BA 591R	BA 592R	Red	190	60
BA 390G	BA 390GS	BA 590G	BA 591G	BA 592G	Grün	150	38
BA 390A	BA 390AS	BA 590A	BA 591A	BA 592A	Gelb	250	42
BA 390B	BA 390BS	BA 590B	BA 591B	BA 592B	Blau	150	46
BA 390W	BA 390WS	BA 590W	BA 591W	BA 592W	Weiß	300	56