



Earth-wire screw terminal

for 2.5 to 10 mm²

Description

Devices with metal housings need an earth-wire screw terminal outside and in the connection chamber.

With explosion-proof devices, these terminals must also be safe. Therefore, they are also tested during the type examination of the device.

The PTB does not issue certificates for small accessories. However, all the earth-wire screw terminals presented here have been examined together with complete devices and considered suitable.

- PTB-tested, terminals accept 2 x 10 mm² (DBSA 0116), 2 x 4 mm² (DBSA 0129 D and 0113) or 2.5 mm² (DBSA 0130).
- Easy mounting by pressing into a pocket hole (H9 = twist drill precision)
- Knurled trunnion offers good contact, safe snug fit and twisting protection
- Auxiliary measures against twisting, such as a milled shoulder, sprue or twisting protection part, are not required.
- Twisting protection of clamping saddle through square profile.
- Loosening protection of the screw through lock washer
- Clamping body galvanised and passivated steel; screw, saddle and lock washer made of VA
- All versions are also available completely made of VA
- No possible thread deformation in trunnion, since solid material
- All types with an optional impressed earth symbol (DIN 40011)

Earth-wire screw terminal

Type	Order No.:	
DBSA 0116	10-90-32	(formerly 1298)
DBSA 0116 VA	10-90-33	(formerly 1299)
DBSA 0113	10-90-34	(formerly 1134)
DBSA 0113 VA	10-90-35	(formerly 1135)
DBSA 0129 D	10-90-36	(formerly 1292)
DBSA 0129 D VA	10-90-37	(formerly 1296)
DBSA 0130	10-90-38	(formerly 1304)
DBSA 0130 VA	10-90-39	(formerly 1305)

If you desire version with earth symbol, please indicate in clear text.



Scale 1:1

